

Technical data

# HD 35 VV



**Tandem rollers Series HD CompactLine**  
Tandem roller with two vibrating roller drums

**H286**

## HIGHLIGHTS

- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Simple, intuitive and language-neutral operation
- > Compact dimensions
- > Ergonomic driver platform
- > Easy transport, simple loading

## TECHNICAL DATA HD 35 VV (H286)

## Weights

Operating weight with ROPS	kg	2755
Max. operating weight	kg	3570
Static linear load, front/rear	kg/cm	11,3/11,6
French classification, value/class		11,6/PV3

## Machine dimensions

Total length	mm	2530
Height loading, min.	mm	1755
Centre distance	mm	1700
Total width	mm	1310
Maximum working width	mm	1250
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2370

## Drum dimensions

Drum width, front/rear	mm	1200/1200
Drum diameter, front/rear	mm	720/720
Drum thickness, front/rear	mm	15/15
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50

## Diesel engine

Manufacturer		KUBOTA
Model		D1803-M-DI-CT02
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		24,4/33,2/2600
Power SAE J1995, kW/HP/rpm		24,4/32,7/2600
Exhaust emission standard		MEE IV
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

## Travel drive

Speed, infinitely variable	km/h	0 - 12,0
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, level I/II	Hz	67/52
Vibration frequency, rear, level I/II	Hz	67/52
Amplitude, front, level I/II	mm	0,52/0,52
Amplitude, rear, level I/II	mm	0,52/0,52
Centrifugal force, front, level I/II	kN	52/32
Centrifugal force, rear, level I/II	kN	52/32

## Steering

Pendulum angle +/-	°	8
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	42
---------------------	---	----

## Tank capacity/filling capacity

Water tank, capacity	L	180
----------------------	---	-----

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

## EQUIPMENT

3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Left/right handrails | Battery isolation switch | Pressure water sprinkling system | Driver's platform with access from both sides | Hydrostatic steering | Vibration-isolated driver's platform | Track offset | Central lifting bracket | Plastic scraper, folding | ROPS, folding

## OPTIONAL EQUIPMENT

Protective roof | Edge pressing and cutting equipment | Track indicator | Water sprinkling system edge pressing and cutting equipment | Back-up alarm | Working spotlights | Rotating beacon | Telematics system