

Technical data

HD 50 VT



Tandem rollers Series HD CompactLine
Tandem roller with vibrating roller drum and set of wheels

H295

HIGHLIGHTS

- > Simple, intuitive and language-neutral operation
- > Easy transport, simple loading
- > Ergonomic driver platform
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Compact dimensions

TECHNICAL DATA HD 50 VT (H295)

Weights

Operating weight with ROPS	kg	4100
Empty weight without cab, without ROPS	kg	3750
Max. operating weight	kg	5100
Axle load, front/rear	kg	2125/1975
Static linear load, front	kg/cm	15,4
French classification, value/class		10,0/VT0
Wheel load per tyre, rear	kg	493,75

Machine dimensions

Total length	mm	2896
Total height with ROPS	mm	2594
Height loading, min.	mm	1829
Centre distance	mm	1950
Total width	mm	1506
Maximum working width	mm	1380
Ground clearance, centre	mm	302
Kerb clearance, left/right	mm	720/720
Turning radius, inside	mm	2710

Drum dimensions

Drum width, front	mm	1380
Drum diameter, front	mm	898
Drum thickness, front	mm	16
Drum type, front		Smooth/non-split
Track offset, left/right	mm	0/50

Tyre dimensions

Tyre size, rear		10.5/80-16
Width over tyres, rear	mm	1276
Number of tyres, rear		4

Diesel engine

Manufacturer		KUBOTA
Model		V2403-M-DI-E3B
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		36,5/49,6/2700
Power SAE J1349, kW/HP/rpm		36,5/48,9/2700
Exhaust emission standard		MEE IV
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40

Vibration

Vibration frequency, front, level I/II	Hz	57/48
Amplitude, front, level I/II	mm	0,51/0,31
Centrifugal force, front, level I/II	kN	58/35

Steering

Pendulum angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	73
Water tank, capacity	L	260
Additive tank, capacity	L	18

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Left/right handrails | Pressure water sprinkling system | Driver's platform with access from both sides | Hydrostatic steering | Vibration-isolated driver's platform | Track offset | Plastic scraper, folding | ROPS, folding

OPTIONAL EQUIPMENT

Protective roof | Edge pressing and cutting equipment | Track indicator | Water sprinkling system edge pressing and cutting equipment | Back-up alarm | Working spotlights | Rotating beacon