

Technical data

HC 110 P



Compactors Series HC
Compactor with padfoot drum

H294

HIGHLIGHTS

- > Engine with best in class power and powerful ECO mode
- > 3-point articulation for outstanding traction and off-road mobility
- > High compaction performance
- > Intuitive and language-neutral operation
- > Easy maintenance and servicing
- > Excellent view of the machine and the construction site

TECHNICAL DATA HC 110 P (H294)

Weights

Operating weight with cab	kg	11980
Operating weight with ROPS	kg	11650
Empty weight without cab, without ROPS	kg	11005
Max. operating weight	kg	12080
Axle load, front/rear	kg	6760/5220
Axle load at max. operating weight, front/rear	kg	6810/5270
Static linear load, front	kg/cm	31,59
French classification, value/class		41,5/VPM3
Wheel load per tyre, rear	kg	2610

Machine dimensions

Total length	mm	5926
Total height	mm	3061
Height loading, min.	mm	2238
Centre distance	mm	2992
Total width	mm	2282
Maximum working width	mm	2140
Ground clearance, centre	mm	448
Kerb clearance, left/right	mm	500/500
Turning radius, inside	mm	3883
Slope angle, front/rear	°	45/27

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1707
Drum thickness, front	mm	15
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

Tyre dimensions

Tyre size, rear		AW 23.1-26 8 PR
Width over tyres, rear	mm	2140
Number of tyres, rear		2

Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PTE
Cylinders, quantity		4
Power SAE J1995, kW/HP/rpm		101,0/135,4/2000
Exhaust emission standard		EU Stage IIIA / EPA Tier 3
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust emissions category, Brazil		MAR-I
Exhaust gas after-treatment		-

Travel drive

Speed, working gear	km/h	0-8,5
Speed, transport gear	km/h	0-11,6
Gradeability, with/without vibration	%	53/59

Vibration

Vibration frequency, front, level I/II	Hz	30/35
--	----	-------

Vibration

Amplitude, front, level I/II	mm	1,80/0,80
Centrifugal force, front, level I/II	kN	250/145

Steering

Steering angle +/-	°	33
Pendulum angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	270
---------------------	---	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	
Sound power level L(WA), representative measurement	db(A)	110

EQUIPMENT

Dashboard with displays, indicator lights and switches | Driver's platform with access on one side | Vibration-isolated driver's platform | Seat length adjustment | 1 drive lever | ECO mode | Tilttable engine hood | Hydrostatic steering | 3-point articulation | Emergency stop | Adjustable scraper | Back-up alarm | Battery isolation switch

OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Driver's seat in black imitation leather; comfort equipment | Fuel prefilter | Process data interface for third-party provider systems, asphalt construction | Speedometer | Automatic vibration system | Rotating beacon |