

Technical data

HD 10 VO



Tandem rollers Series HD CompactLine

Tandem roller with vibration and oscillation drum

H262

HIGHLIGHTS

- > Simple, intuitive and language-neutral operation
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Ergonomic driver platform
- > Compaction with oscillation
- > Compact dimensions

TECHNICAL DATA HD 10 VO (H262)

Weights

Operating weight with ROPS	kg	2525
Maximum operating weight	kg	3240
Static linear load, front/rear	kg/cm	12,1/13,2
French classification, value/class		13,2/PV3

Machine dimensions

Total length	mm	2530
Total height with ROPS	mm	2475
Height loading, min.	mm	1752
Centre distance	mm	1700
Total width	mm	1110
Maximum working width	mm	1050
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2470

Drum dimensions

Drum width, front/rear	mm	1000/1000
Drum diameter, front/rear	mm	720/720
Drum thickness, front/rear	mm	15/15
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50

Diesel engine

Manufacturer		Kubota
Model		D1503
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		22,9/31,1/2700
Power SAE J1349, kW/HP/rpm		22,9/30,7/2700
Exhaust emission standard		EU Stage IIIA
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h	0-12,0
Gradeability, with/without vibration	%	35/40

Vibration

Vibration frequency, front, I/II	Hz	65/51
Amplitude, front, I/II	mm	0,45/0,45
Centrifugal force, front, I/II	kN	43/26

Oscillation

Oscillation force, rear, I/II	kN	39/23
Oscillation frequency, rear, I/II	Hz	38/29
Tangential amplitude, rear, I/II	mm	1,34/1,34

Steering

Pendulum angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	42
---------------------	---	----

Tank capacity/filling capacity

Water tank, capacity	L	180
----------------------	---	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with access from both sides | Drive lever, left and right | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Central lifting bracket | ROPS, rigid

OPTIONAL EQUIPMENT

Plastic scraper, folding | Edge pressing and cutting equipment | Track indicator | Chip spreader | Thermal aprons | All-wheel lock | Anti-freeze injection system | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Working spotlights | Drum edge lighting | Water drain valve | Towing eye, front | Tow hitch | V-belt protection