

Technical data

HC 200 C P



Compactors Series HC
Compactor with padfoot drum

H257

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 200 C P (H257)

Weights

Operating weight with cab	kg lbs	19645 43,317
Operating weight with ROPS	kg lbs	19310 42,579
Empty weight without cab, without ROPS	kg lbs	18445 40,671
Maximum operating weight	kg lbs	20400 44,982
Axle load, front/rear	kg lbs	13560/6085 29,900/13,417
Axle load at maximum operating weight, front/rear	kg lbs	13590/6810 29,966/15,016
Static linear load, front	kg/cm lbs/in	63,36 354.8
French classification, value/class		87,68/VPM5
Wheel load per tire, rear	kg lbs	3042,5 6,709

Machine dimensions

Total length	mm in	6610 260.2
Total height with cab	mm in	3046 119.9
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3312 130.4
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	453 17.8
Curb clearance, left/right	mm in	469/469 18.5/18.5
Turning radius, inside	mm in	4278 168.4
Slope angle, front/rear	°	33,6/25,7

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1803 71.0
Drum thickness, front	mm in	35 1.4
Drum type, front		Padfoot
Height of the padfeet	mm in	112 4.4
Padfeet, quantity		140

Tire dimensions

Tire size, rear		TR 23.1/18-26 12 PR
-----------------	--	---------------------

Tire dimensions

Width over tires, rear	mm in	2140 84.3
Number of tires, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 2012 L06 2V
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		150,0/203,9/2000
Power SAE J1349, kW/HP/rpm		150,0/201,2/2000
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust emissions category, EU		EU Stage IIIA
Exhaust emissions category, USA		EPA Tier 3
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h mph	0 - 11,5 0.0 - 7.1
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	59/66

Vibration

Vibration frequency, front, I/II	Hz vpm	27/30 1,620/1,800
Amplitude, front, I/II	mm in	2,10/1,20 .083/.047
Centrifugal force, front, I/II	kN lbs	350/250 78,750/56,250

Steering

Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	336 88.8
---------------------	----------	-------------

Sound level

Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (2-fold) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, automatic | Steel scraper, for padfoot drum

OPTIONAL EQUIPMENT