

Technical data

HC 130 P



Compactors Series HC
Compactor with padfoot drum

H255

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 130 P (H255)

Weights

Operating weight with cab	kg	13190
Operating weight with ROPS	kg	12840
Empty weight without cab, without ROPS	kg	12250
Max. operating weight	kg	15140
Axle load, front/rear	kg	7925/5265
Axle load for max. operating weight, front/rear	kg	9000/6140
Static linear load, front	kg/cm	37,03
French classification, value/class		48,04/VPM3
Wheel load per tyre, rear	kg	2632,5

Machine dimensions

Total length	mm	6117
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Total height with plastic protective roof	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	33,7/23,7

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1707
Drum thickness, front	mm	20
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

Tyre dimensions

Tyre size, rear		TR 23.1/18-26 12 PR
Width over tyres, rear	mm	2154
Number of tyres, rear		2

Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PTE
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		101,0/137,3/2000
Power SAE J1349, kW/HP/rpm		101,0/135,4/2000
Exhaust emission standard		EU Stage IIIA / EPA Tier 3
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h	0 - 11,9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	55/61

Vibration

Vibration frequency, front, I/II	Hz	30/36
Amplitude, front, I/II	mm	1,80/0,85
Centrifugal force, front, I/II	kN	262/182

Steering

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	280
---------------------	---	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Steel scraper, for padfoot drum

OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Seat belt monitoring device | Auxiliary heater | Radio | Tachograph | Bluetooth interface for Smart Doc | Dozer blade | Automatic engine stop | Camera system | JDLink | Working spotlights | Engine hood with electrical release mechanism | Coming Home function