

Technical data

HD 10 VO



Tandem rollers Series HD CompactLine

Tandem roller with vibration and oscillation drum

H262

HIGHLIGHTS

- > Simple, intuitive and language-neutral control
- > Excellent view of drum edge, machine and construction site environment
- > Ergonomic driver platform
- > Compaction with oscillation
- > Compact dimensions

TECHNICAL DATA HD 10 VO (H262)

Weights

Operating weight with ROPS	kg lbs	2525 5,568
Maximum operating weight	kg lbs	3240 7,144
Static linear load, front/rear	kg/cm lbs/in	12,1/13,2 67.8/73.9
French classification, value/class		13,2/PV3

Machine dimensions

Total length	mm in	2530 99.6
Total height with ROPS	mm in	2475 97.4
Height loading, min.	mm in	1752 69.0
Center distance	mm in	1700 66.9
Total width	mm in	1110 43.7
Maximum working width	mm in	1050 41.3
Ground clearance, center	mm in	280 11.0
Curb clearance, left/right	mm in	570/570 22.4/22.4
Turning radius, inside	mm in	2470 97.2

Drum dimensions

Drum width, front/rear	mm in	1000/1000 39.4/39.4
Drum diameter, front/rear	mm in	720/720 28.3/28.3
Drum thickness, front/rear	mm in	15/15 0.6/0.6
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	0/50 0.0/2.0

Diesel engine

Manufacturer		Kubota
Model		D1503
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		22,9/31,1/2700
Power SAE J1349, kW/HP/rpm		22,9/30,7/2700
Exhaust emission standard		EU Stage IIIA
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h mph	0-12,0 0.0-7.5
Gradeability, with/without vibration	%	35/40

Vibration

Vibration frequency, front, I/II	Hz vpm	65/51 3,900/3,060
Amplitude, front, I/II	mm in	0,45/0,45 .018/.018
Centrifugal force, front, I/II	kN lbs	43/26 9,675/5,850

Oscillation

Oscillation force, rear, I/II	kN lbs	39/23 8,775/5,175
Oscillation frequency, rear, I/II	Hz vpm	38/29 2,280/1,740
Tangential amplitude, rear, I/II	mm in	1,34/1,34 .053/.053

Steering

Pendulum angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	42 11.1
Water tank, capacity	L Gal	180 47.6

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with access from both sides | Drive lever, left and right | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Central lifting bracket | ROPS, rigid

OPTIONAL EQUIPMENT

Plastic scraper, folding | Edge pressing and cutting equipment | Track indicator | Chip spreader | Thermal aprons | All-wheel lock | Anti-freeze injection | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Working spotlights | Drum edge lighting | Water drain valve | Towing eye, front | Tow hitch | V-belt protection